

Plug-In

Sunlite LED PLL Recessed Plug & Play Long Twin Light Bulb, 17 Watt (FT40DL/40W BIAX Replacement) 2350 Lumens, 2G11 4-Pin Base Light-Tube, UL Listed, ROHS Compliant, 3000K Warm White, 1 Count

Plug and Play

DESCRIPTION:

Upgrade your fluorescent bulbs with energy-efficient LED plug and play light bulbs, a direct replacement with no ballast bypass required. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours, you will be required to replace difficult-to-reach bulbs less often. You will save maintenance costs and save energy at the same time. Our PLL bulbs feature a 2G11 4-Pin base and can be used for both commercial/residential locations. Please shop with confidence as these led bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified. Unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.

FEATURES:

- **UPGRADE TO LED** - Replace your inefficient fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Can be used in enclosed fixtures and has a High Color Rendering Index rating of 82.
- **PLUG AND PLAY** - These Sunlite led bulbs replace inefficient fluorescent light bulbs with no bypass required. For use with electronic ballasts only. You can find a list of tested compatible ballasts included in the description in this listing.
- **ENERGY EFFICIENT** – With a 3000K warm white color temperature each bulb Produces 2350 lumens of light while only using 17 watts of electricity! Annual energy costs are a low \$2.05 (Based on 3 hours/day at \$0.11/kWh).
- **UL LISTED AND ROHS COMPLIANT** - These Sunlite bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also ROHS Certified unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.
- **MULTI USE** – With a lifespan of up to 50,000 hours our LED PLL Bulbs will retrofit into your existing troffers Ceiling Lights. Dimensions: 22.17" H x .67" D.

SPECIFICATIONS:

General Characteristics

Bulb Shape	FT
Average Rated Hours	50000
Finish	White
Base	4-Pin (2G11)
Average Life Span Years	46
Dimmable	No
Material	Glass

Electrical Characteristics

Amps	0.142
Watts	17
Equivalent Wattage	40
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	2350
Color Rendering Index CRI	82
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	140°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
DLC	Yes
DLC Number	DDDKOK
DLC Classification	Standard

Product Dimensions

MOL (in)	22.48
Diameter (in)	0.69
Item Dimension (in)	(W) 1.8 (H) 1.4 (D) 22.6
Package Dimension (in)	(W) 2 (H) 1.5 (D) 23
Package Weight (lb)	0.95

Product Data

Case Unit Rate	10
Pack Size	1
Item UPC	653703810614
Warranty Years	5
Package Type	Box