

T Series

Sunlite 81259-SU LED T36 Super Bright High Lumen Corn Light Bulb, 45 Watts (525W Equivalent) 5800 Lumens, Medium e26 Base, 120-277 Multi Volt, Non-Dimmable, 30K-Warm White, UL Listed-Wet Location

High Lumen Lamps

DESCRIPTION:

Sunlite Bullet LED T36 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time. Each bulb contains 106 LEDs giving off a bright 5800 lumen at 3000K Warm White color temperature. Provides as much light as a 525 watt bulb while only using 45 watts of electricity. With a 50000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications. UL Listed for Damp Location Installation. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). The 220 degree beam angle gives a broader spread than UFO bulbs and more downlight than corn bulbs.



- UPGRADE TO LED These LED T36 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time.
- ENERGY EFFICIENT These bulbs give out as much light as a 525 incandescent watt bulb while only using 45 watts of electricity. Estimated yearly energy cost is a low \$5.42. (Based on 3 hours/day use at \$0.11/kWh)
- HIGH LUMEN OUTPUT LED Bullet Bulbs provide 220 degree lighting coverage giving them a broader spread than UFO bulbs and more downlight than corn bulbs. Each bulb contains 106 LEDs and gives off a bright 5800 lumen output with Warm White 3000K color temperature.
- *LONG LIFE With a 50,000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications.
- UL LISTED These bulbs are UL Listed for Wet Location installations. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). For use in 120-277 volt fixtures. Ingress protection (IP) rating of 44.



IP44 (1 mm solids, Splashing of

PC Cover & Aluminum

water)

No





SPECIFICATIONS:

0	01	4 4
(-onorai	Charact	IDIIETICE
OCHCI ai	Offial act	ici istics

Bulb ShapeT36Average Rated Hours50000FinishWhiteBaseMedium Screw (E26)

Average Life Span Years 46

Ingress Protection

Dimmable

Material

Electrical Characteristics

Watts 45
Volts 120-277
Equivalent Wattage 525
LED Chip Manufacturer 2835
Power Factor 0.9
Temperature -20-45?

Light Characteristics

Lumens Brightness5800Color Rendering Index CRI80

Emitted Color Warm White

Color Temperature Kelvin3000KBeam Angle220°Flicker<30%</th>

Additional Features

Safety Rating Mark UL Listed - Wet Location

Product Dimensions

 MOL (in)
 9.45

 Diameter (in)
 5.51

Package Dimension (in) (W) 10 (H) 5.9 (D) 5.7 Package Weight (lb) 1.3

Product Data

 Case Unit Rate
 6

 Pack Size
 1

 Item UPC
 653703812595

Warranty Years 3
Package Type Box

