

Retrofit your space with our LED retrofit downlight kit. It is developed utilizing the latest in LED technology. With a lifetime of 30,000 hours, it is sure to stand the test of time. Featuring a warm temperature of 3000 Kelvin, it gives your space a warm ambiance with a homey feel. UL listed for damp locations, it can be installed indoors or outdoors and will stand against the elements.

### **General Characteristics**

| Fixture Life Hours      | 50000 Hours   |
|-------------------------|---------------|
| Material                | Aluminum & PC |
| Lens Finnish            | Frosted       |
| Finish                  | White         |
| Life (based on 3hr/day) | 45.700000000  |
| Energy Star             | True          |
| Dimmable                | True          |
|                         |               |

### **Electrical Characteristics**

| Watts | 12  |
|-------|-----|
| Volts | 120 |

#### **Light Characteristics**

| Brightness           | 1000 Lumens         |
|----------------------|---------------------|
| Color Accuracy (CRI) | 80                  |
| Light Appearance     | CCT Tunable         |
| Color Temperature    | 27K/30K/35K/40K/50K |

### **Product Dimensions**

| Size          | 4"   |
|---------------|------|
| Diameter (in) | 4.84 |

## **Product Data**

| Item Number             | 82083-SU           |
|-------------------------|--------------------|
| Case Quantity           | 24.000000          |
| Barcode on SKU          | 653703820835       |
| Brand                   | Sunlite            |
| Description             | LFX/EDL/4R/12W/SCT |
| Energy Star File Number | 2375962            |

# **Additional Features**

ENERGY STAR CERTIFIED

True

## **Fixture Characteristics**

| Shape            | Round     |
|------------------|-----------|
| Number of Lights | 1 - Light |
| Mounting         | Recessed  |
| Use Location     | Indoor    |