





Sunlite 87742-SU 7.5-Inch Round LED Mini Flat Panel Fixture, 15 Watts (60W Equivalent), 120 Volts, Color Tunable (30K/40K/50K), 800 Lumens, Dimmable, 50,000 Hour Life Span, ETL Listed, Brushed Nickel Finish

- SLIM AND STYLISH The Sunlite 7.5" Round LED Mini Flat Panel Fixture is a stylish addition to any décor. The slim disc design features an aluminum body with white trim and a shatter-resistant frosted lens. Each fixture is 1.13 inches high and 7.33 inches in diameter.
- COLOR TUNABLE This tunable fixture features innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back.
- DIMMABLE Fixture can be dimmed when installed with an LED compatible dimmer. Output is a bright 800 lumens (60 watt equivalent) while only using 15 watts of electricity. High color rendering at 90 CRI.
- LONG LIFE SPAN This dimmable indoor fixture has a 50,000 hour life span for years of reliable service.
- ETL LISTED ETL Listed for Wet Location installation (IP20). Each fixture includes installation hardware and instructions.

LFX/DISC/SCT/7.5"/15W/D/BN LED DISC LIGHT SUNLITE

General Characteristics

Fixture Life Hours
Material
Lens Material
Lens Finish
Finish
Lumens Per Watt (LPW)
Life (based on 3hr/day)
Estimated Energy Cost
Safety Rating
Ingress Protection
Dimmable
Dimming Type
Fixture Characteristics
Shape
Number of Lights
Mounting
Use Location
Electrical Characteristics
Watts
Volts
Equivalent Watts
LED Chip Manufacturer
Power Factor

Operating Temperature
Light Characteristics

Brightness Color Accuracy (CRI) Light Appearance Color Temperature

Beam Angle

Product Dimensions

Size Height (in) Diameter (in) Item Dimensions (in) Package Dimensions (in)

Product Data

Item Number Case Quantity Barcode on SKU Barcode on Case Brand Description 50000 Hours Aluminum Polycarbonate White Brushed Nickel 53.33 45.7 \$1.81 per Year ETL Listed - Wet Location IP20 True Forward/Reverse Phase (Triac/Elv)

Round 1 - Light Surface

Indoor

15 120 60 SMD2835 0.9 -20°+45°

800 Lumens 90 CCT Tunable 30K/40K/50K 110°

7.25" 1.125 7.25 (W) 7.33 (H) 1.11 (D) 7.33 (W) 7.64 (H) 1.65 (D) 7.64

87742-SU 24 653703877426 10653703877423 SUNLITE LFX/DISC/SCT/7.5'/15W/D/BN

