

T Series**Sunlite 88040 4FT LED T8 Glass Tube Light Bulb (Type A+B), 18W, 120-277V, 2300 Lmn, 2-Pin G13 Base, Single or Double-Ended Ballast, Dimmable, UL Listed, 6500K Daylight, F32T8, F48T8 Replacement, 25 PK**

Hybrid Type A + B

DESCRIPTION:

Sunlite's LED T8 Shatterproof Glass Tube Bulb is the perfect lighting solution to any residential or commercial setting. With a Type A+B design, it can be used with electronic ballasts or directly wired to AC power, making it ideal for retrofitting or new installations. Constructed with shatterproof glass, this advanced light bulb sets a new standard for safety and resilience. Its long-life LED technology offers up to 50,000 hours of service, and it can be easily installed in various commercial spaces with its medium 2-Pin G13 Base feature. Additionally, it is UL Listed for damp location and tested for safety and quality, making it a reliable choice for offices, schools, and retail spaces. Glass tubes with shatterproof coating. Bulb Dimensions: 1.10" H x 47.16" W.

FEATURES:

- **SINGLE OR DOUBLE ENDED BALLAST** - The single ended ballast feature is compatible with instant-start ballasts, while the double ended ballast option can work with both instant-start and programmed-start ballasts. This allows you to choose the most convenient and cost-effective option for your space.
- **EASY INSTALLATION** – With its Type A+B design for the bulb, it can be used with either electronic ballasts (Type A) or directly wired to AC power (Type B), making it an ideal choice for retrofitting existing bulbs or for new installations. Its medium 2-Pin G13 Base feature makes it easy to install in a variety of applications, including commercial and industrial spaces, warehouses, offices, and more.
- **LONG LIFE & DIMMABLE** - Long life LED technology means up to 50,000 hours of reliable service while only using 18 watts of electricity, which means you'll need to replace difficult to access bulbs less often. The lighting output can be dimmed when connected to an LED-compatible dimmer switch (0-10v), allowing you to adjust the brightness to give you the bright, crisp illumination you need to see in any commercial space.
- **DAYLIGHT** - At 6500K these daylight bulbs provide natural lighting in bedrooms, living spaces or anywhere you want to a realistic lighting. Constructed with shatterproof glass, this advanced light bulb sets a new standard for safety and resilience.
- **UL LISTED** – UL Listed for damp location. Tested for safety and quality that can be used in various settings, including office buildings, schools, and retail spaces. Glass tubes with shatterproof coating. Bulb Dimensions: 1.10" H x 47.16" W.

SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|--------------------|
| Bulb Shape | Linear Tube |
| Average Rated Hours | 50000 |
| Finish | Frosted |
| Base | Medium 2-Pin (G13) |
| Average Life Span Years | 46 |
| Dimmable | Yes |
| Dimming Type | Not Dimmable |
| Material | Glass |

Electrical Characteristics

| | |
|------------------------------|--------------|
| Amps | .185 |
| Watts | 18 |
| Volts | 120-277 |
| Equivalent Wattage | F32T8, F48T8 |
| LED Chip Manufacturer | SMD2835 |
| Power Factor | >0.9 |
| Temperature | -4°F - 113°F |

Light Characteristics

| | |
|----------------------------------|----------|
| Lumens Brightness | 2300 |
| Color Rendering Index CRI | 83 |
| Emitted Color | Daylight |
| Color Temperature Kelvin | 6500K |
| Beam Angle | 320° |

Additional Features

| | |
|-----------------------------------|---------------------------|
| Safety Rating Mark | UL Listed - Damp Location |
| UL Rated Enclosed Fixtures | Yes |
| Safety Rated For USA | Yes |
| DLC | Yes |
| DLC Classification | Standard |
| Mercury Free | Yes |

Product Dimensions

| | |
|----------------------|--------|
| Size | 4' |
| MOL (in) | 47.16" |
| Diameter (in) | 1.10 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 25 |
| Pack Size | 1 |
| Item UPC | 653703880402 |
| Warranty Years | 5 |