



Sunlite 88271-SU LED PLD Light Bulb, 9 Watts (26W Equivalent), 950 Lumens, G24q Base, Ballast Dependant, CFL Replacement, UL Listed, 30K - Warm White 1 Pack

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with 3000K color temperature at 3000K. Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.

- **UPGRADE TO LED** - Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage.
- **NO FLICKERING OR BUZZING** - LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with Warm White color temperature at 3000K.
- **ENERGY EFFICIENT** - These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. That's a 65% energy savings. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- **LONG LIFE SPAN** - Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- **A SAFER CHOICE** - Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.

General Characteristics

Bulb	PLD
Lamp Life Hours	50000 Hours
Material	Plastic
Bulb Finish	White
Life (based on 3hr/day)	45.7000000000 Years
Safety Rating	UL Listed - Damp Location
Rated For Totally Enclosed Fixtures	True
DLC Classification	Standard

Electrical Characteristics

Watts	9
Equivalent Watts	18
Power Factor	0.9
Temperature	-20° to 45° C

Light Characteristics

Brightness	950 Lumens
Color Accuracy (CRI)	82
Light Appearance	Warm White
Color Temperature	3000K
Beam Angle	270°

Product Dimensions

MOL (in)	6.57
Item Dimensions (in)	(W) 1.34 (H) 6.61 (D) 1.4

Product Data

Item Number	88271-SU
Case Quantity	12.000000
Pack Size	1 Pack
Barcode on SKU	653703882710
Brand	Sunlite
Description	PLD/LED/IS/9W/30K/V2
DLC File Number	PL7UM4E2B75T
Warranty	5 Years

Additional Features