



Sunlite 88683-SU Tunable LED Mission Style Outdoor Fixture, 12 Watts (75W Equivalent), 800 Lumens, For Porch, Patio, Decks, Black Finish, Opaque White Lens, ETL Listed for Wet Location Installation, Color Temperature Tunable 3000K/4000K/5000K

Add a classic touch to any home or business with this Sunlite Tunable LED Wall Fixture. The Mission-Style design black metal frame holds an opaque white polycarbonate lens. This tunable fixture features innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. Built-in photocell for automatic dusk-to-dawn operation. With energy efficient LEDs this a no maintenance lighting solution for residential or commercial use. Long 50,000 hour lifespan for years of maintenance-free service. Output is a bright 800 lumens (75 watt equivalent) while only using 12 watts of electricity. Estimated annual energy costs are \$1.45 based on 3hrs/day at \$0.11/KwH. Fixture measures 7.95 in wide, 9.52 in high, and 4.48 in deep. ETL Listed for wet location installation. IP42 Rated.

- MSSION STYLE Add a classic touch to any home or business with this Sunlite Tunable LED Wall Fixture. The Mission-Style design black metal frame holds an opaque white polycarbonate lens. Output is a bright 800 lumens (75 watt equivalent) while only using 12 watts of electricity.
- COLOR TUNABLE This tunable fixture features innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back.
- BUILT-IN PHOTOCELL Built-in photocell for automatic duskto-dawn operation. Includes cap to cover the sensor for manual wall switch operation.
- LONG LIFE SPAN Long 50,000 hour lifespan for years of maintenance-free service. Estimated annual energy costs are \$1.45 based on 3hrs/day at \$0.11/KwH.
- ETL LISTED Tested to meet ETL's strict safety and design standards for wet location installation. IP42 Rated. Fixture measures 7.95 in wide, 9.52 in high, and 4.48 in deep.

General Characteristics

Fixture Life Hours	50000 Hours
Material	Aluminum & Steel
Lens Finnish	White
Finish	Black
Life (based on 3hr/day)	45.700000000
Safety Rating	ETL Listed - Wet Location
Ingress Protection	IP42 (1 mm solids, Dripping water when tilted 15°)

Electrical Characteristics

Watts	12
Volts	120
Equivalent Watts	75
LED Chip Manufacturer	DOB
Power Factor	0.9
Operating Temperature	45?

Light Characteristics

Brightness	800 Lumens
Color Accuracy (CRI)	80
Light Appearance	CCT Tunable
Color Temperature	30K/40K/50K
Beam Angle	120°

Product Dimensions

Item Dimensions (in)

(W) 7.95 (H) 9.52 (D) 4.48

Product Data

Item Number	88683-SU
Case Quantity	6.000000
Barcode on SKU	653703886831
Brand	Sunlite
Description	LFX/WS/SCT/RT/12W/SG/ BK/PC

Additional Features

UL RATING

ETL Listed - Wet Location

Fixture Characteristics

Shape	Rectangle
Number of Lights	1 - Light
Mounting	Wall
Use Location	Outdoor

744 Clinton St. Brooklyn, NY 11231 | 718.768.7000

www.sunlite.com