

LED Replacement Lamps

LED PAR38 Indoor/Outdoor Commercial Directional Lamps



Project Name _____

Date _____ Type _____

Notes _____

For indoor and outdoor applications, Current's entire PAR38 portfolio offers a multitude of wattage options with a high light output. These range from standard to high light output.

PERFORMANCE HIGHLIGHTS:

PAR38 Lamps	
Light Output Range:	1050-3100 Lumens
CRI:	80-92
CCT:	2700K, 3000K, 3500K, 4000K & 5000K
Input Voltage:	120-277
Efficiency:	Up to 97 LPW
Wattage:	12W, 15W, 18W & 32W
Life:	Up to 25,000 hours L70
Temperature Rating:	-20°C to 45°C
Location Rating:	Damp & Wet

LIMITED WARRANTY

3 years

FEATURES:

- Halogen-like color color
- Available in different beam patterns
- These lamps are energy efficient, contain no lead or mercury

BENEFITS:

Energy + Cost Savings

- For example, using only 18 watts of energy, save over \$280 in energy costs over the rated life of the lamp versus a standard 120-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources
- Ideal for both indoor and outdoor applications
- UL wet rated for outdoor applications

LEARN MORE:

To learn more about saving money and energy, go to www.gecurrent.com.

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED Replacement Lamps

LED PAR38 Indoor/Outdoor Commercial Directional Lamps

Spec Table

SALE on GE Lighting @ www.BulbAmerica.com
take additional 5% Off with coupon code 5PDF

Project Name _____


Date _____ Type _____

Notes _____


Directional Lamps (PAR38 - Visual Comfort Lens™)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	MOL (in)	Lumens (Initial)	CBCP	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³	Additional Information	
PAR38 - Low Glare - Visual Comfort Lens™																		
	E26	12	92971	LED12D38W3827/40	120	6	5.31	1050	2300	2700	81	100	25,000	Yes	★	Damp	Flood, 40° beam, White	
	E26	12	92969	LED12D38W3827/25	120	6	5.31	1050	5500	2700	80	100	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White	
	E26	12	92972	LED12D38W3830/25	120	6	5.31	1050	5500	3000	81	100	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White	
	E26	12	92973	LED12D38OW3830/40	120	6	5.31	1050	2300	3000	80	100	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	12	9313599	LED12D38OW3930/25	120	6	5.31	1050	4800	3000	90	100	25,000	Yes	-	Damp	Narrow Flood, 25° beam, White	
	E26	18	92950	LED18D38OW3827/25	120	6	5.31	1550	5800	2700	81	120	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	18	92923	LED18D38W3927/25	120	6	5.31	1250	4900	2700	92	100	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White	
	E26	18	92958	LED18D38OW3827/40	120	6	5.31	1550	3800	2700	81	120	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	18	92926	LED18D38W3927/40	120	6	5.31	1250	2900	2700	92	120	25,000	Yes	★	Damp	Flood, 40° beam, White	
	E26	18	92927	LED18D38W3930/15	120	6	5.31	1350	15000	3000	92	75	25,000	Yes	★	Damp	Spot, 15° beam, White	
	E26	18	92961	LED18D38W3830/15	120	6	5.31	1750	20000	3000	81	150	25,000	Yes	★	Damp	Spot, 15° beam, White	
	E26	18	93096546	LED18D38S3830/15	120	6	5.31	1750	20000	3000	80	150	25,000	Yes	-	Damp	Spot, 15° beam, Silver	
	E26	18	65727	LED18D38OW3830/25	120	6	5.31	1550	6000	3000	80	150	25,000	Yes	★	Wet	Narrow Flood, 25° beam, Black	
	E26	18	93096804	LED18D38OS3830/25	120	6	5.31	1550	6000	3000	80	150	25,000	Yes	-	Wet	Narrow Flood, 25° beam, Silver	
	E26	18	92963	LED18D38OW3830/25	120	6	5.31	1550	6000	3000	81	120	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	18	92933	LED18D38W3930/25	120	6	5.31	1350	5200	3000	92	100	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White	
	E26	18	92967	LED18D38OW3830/40	120	6	5.31	1550	4000	3000	81	150	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	18	92934	LED18D38W3930/40	120	6	5.31	1350	3200	3000	92	120	25,000	Yes	★	Damp	Flood, 40° beam, White	
	E26	18	85085	LED18D38OW3835/25	120	6	5.31	1700	6500	3500	81	120	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	18	87917	LED18D38OW3835/40	120	6	5.31	1700	4400	3500	81	150	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	18	93171	LED18D38OW3840/25	120	6	5.31	1700	6500	4000	81	120	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	18	93172	LED18D38OW3840/40	120	6	5.31	1700	4400	4000	81	150	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	18	65730	LED18D38OW3850/25	120	6	5.31	1700	6500	5000	81	120	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	18	65731	LED18D38OW3850/40	120	6	5.31	1700	4400	5000	81	150	25,000	Yes	★	Wet	Flood, 40° beam, White	

Directional Lamps (PAR38 - High Output)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	MOL (in)	Lumens (Initial)	CBCP	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³	Additional Information	
PAR 38 - High Output - TIR Lens																		
	E26	32	75447	LED32DP38W830/15	120	6	5.12	3000	26000	3000	82	250	25,000	Yes	★	Wet	Spot, 15° beam, White	
	E26	32	88801	LED32DP38W830/25	120	6	5.12	3000	13000	3000	80	250	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	32	88810	LED32DP38W830/40	120	6	5.12	3000	6000	3000	80	250	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	32	30233	LED32DP38W835/15	120	6	5.12	3100	25000	3500	80	250	25,000	Yes	★	Wet	Spot, 15° beam, White	
	E26	32	30237	LED32DP38W835/25	120	6	5.12	3100	13000	3500	80	250	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White	
	E26	32	30239	LED32DP38W835/40	120	6	5.12	3100	6000	3500	80	250	25,000	Yes	★	Wet	Flood, 40° beam, White	
	E26	32	20109	LED32P38W830/15	120-277	6	5.12	3000	25000	3000	80	250	25,000	-	★	Wet	Spot, 15° beam, White	
	E26	32	20130	LED32P38W830/25	120-277	6	5.12	3000	13000	3000	80	250	25,000	-	★	Wet	Narrow Flood, 25° beam, White	
	E26	32	20137	LED32P38W830/40	120-277	6	5.12	3000	6000	3000	80	250	25,000	-	★	Wet	Flood, 40° beam, White	

Directional Lamps (PAR38 - Value)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	MOL (in)	Lumens (Initial)	CBCP	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³	Additional Information	
PAR38 - TIR Lens																		
	E26	15	32213	LED15DP38830/40	120	6	5.04	1300	2300	3000	81	90	25,000	Yes	★	Wet	Flood, 40° beam, TIR	
	E26	15	93153880	LED15DP38VOW830/35-4PK	120	16	5.31	1300	2300	3000	80	90	15,000	Yes	-	Wet	Flood, 35° beam, TIR, 4 pack	
	E26	16	43076	LED16DP389CW-2P	120	12	5.16	1300	2500	3000	90	120	15,000	Yes	-	Wet	Flood, 35° beam, TIR, 2 pack^	

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Case Qty

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPs

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment. When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.

^ GE Lighting, a Savant company, lamp, distributed by GE Current, a Daintree company.