

# Refresh



Application illustration only, subject lamps not used in photo.

## LED RS Can Downlights

GE LED RS Can Downlights are the perfect retrofit solution to give an updated look to ceilings with recessed lighting. Simply replace the existing BR30 lamp with the LED downlight, no tools or wiring required.

### LOW-COST OPERATION

- Uses 80% less energy
- For example, using only 8 watts of energy, saves over \$44 in energy costs over the rated life of a lamp vs. a standard 65 watt incandescent lamp based on \$0.11 per kWh and provides similar light output (700 vs 755 lumens)

### EXCELLENT COLOR RENDERING

- Available with a CRI of 80

### COLOR TEMPERATURE

- Available in 2700K, 3000K and 4000K

### SIMPLE UPGRADE

- Screws into existing fixture
- Provides refreshed look to aged fixtures
- No wiring or tools required
- Upgraded design for 6" option
- Improved installation with torsion springs
- Better fit with reduced MOL for shallower cans
- Alternative friction spring included
- Adjustable for 5" can
- 4" inch GEN 1 design also available

### LONG LIFE

- 25X longer life
- 50,000 hour rated life (L70) vs. Incandescent 2000 hour

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### GE QUALITY AND RELIABILITY

- 5-year limited warranty

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

To learn more about saving money and energy,  
go to: <http://products.currentbyge.com>.



ecomagination<sup>SM</sup>

**current**  
powered by GE



## LED RS Cans

### Downlights

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty*	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
	E26	10	95853	LED10RS4/827E26P	120	12	4.32	700	2700	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment	
			95854	LED10RS4/830E26P	120	12	4.32	700	3000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment	
			35365	LED10RS4/840E26P	120	12	4.32	700	4000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment	
	8	8	19888	LED8DRS6/827	120	4	4.96	700	2700	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment	
			19908	LED8DRS6/830	120	4	4.96	700	3000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment	
			20026	LED8DRS6/840	120	4	4.96	700	4000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment	
			13	20037	LED13DRS6/827	120	4	4.96	1000	2700	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				20048	LED13DRS6/830	120	4	4.96	1000	3000	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks

**current**  
powered by GE

<http://products.currentbyge.com>.

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.

LEDL030 (Rev. 01/08/18)

