

# LUXRITE

HID



## SPECIFICATIONS

HPS  
METAL HALIDE

MODEL	CASE	FINISH	COLOR TEMPERATURE		CRI	OPERATING POSITION
ALL HPS	12	CLEAR	2100K	WARM WHITE	21	UNIVERSAL

MODEL	DESCRIPTION	SHAPE	BASE	WATT	LUMENS	AVERAGE LIFETIME	VOLTS	ANSI
LR20680	LU35/ED17	ED-17	E26	35	2250	16000hrs (14.6yrs)	52	S76
LR20685	LU50/ED17	ED-17	E26	50	4000	24000hrs (21.9yrs)	52	S68
LR20690	LU70/ED17	ED-17	E26	70	6300	24000hrs (21.9yrs)	52	S62
LR20695	LU100/ED17	ED-17	E26	100	9500	24000hrs (21.9yrs)	52	S54
LR20700	LU150/ED17	ED-17	E26	150	16000	24000hrs (21.9yrs)	52	S55
LR20705	LU70/MOGUL	ED-23.5	E39	70	6300	24000hrs (21.9yrs)	52	S62
LR20710	LU100/MOGUL	ED-23.5	E39	100	9500	24000hrs (21.9yrs)	55	S54
LR20715	LU150/MOGUL	ED-23.5	E39	150	16000	24000hrs (21.9yrs)	55	S55
LR20720	LU250/MOGUL	ED-18	E39	250	28500	24000hrs (21.9yrs)	100	S50
LR20725	LU400/MOGUL	ED-18	E39	400	50000	24000hrs (21.9yrs)	100	S51

MODEL	CASE	FINISH	COLOR TEMPERATURE		CRI	OPERATING POSITION
ALL METAL HALIDE	12	CLEAR	4000K	COOL WHITE	70	UNIVERSAL

MODEL	DESCRIPTION	SHAPE	BASE	WATT	LUMENS	AVERAGE LIFETIME	VOLTS	ANSI
LR20640	MH50/U/MED	ED17	E26	50	3400	12000hrs (11yrs)		M110/E (ENCLOSED)
LR20645	MH70/U/MED	ED17	E26	70	5500	12000hrs (11yrs)		M98/E (ENCLOSED)
LR20650	MH100/U/MED	ED17	E26	100	6500	12000hrs (11yrs)		M90/E (ENCLOSED)
LR20655	MH150/U/MED	ED17	E26	150	12000	12000hrs (11yrs)		M102/E (ENCLOSED)
LR20660	MH175/U/MED	ED17	E26	175	14000	12000hrs (11yrs)		M57/E (ENCLOSED)
LR20665	MH175/U/MOGUL	ED28	E39	175	14000	10000hrs (9.1yrs)		M57/E (ENCLOSED)
LR20670	MH250/U/MOGUL	ED28	E39	250	20000	10000hrs (9.1yrs)		M58/E (ENCLOSED)
LR20675	MH400/U/MOGUL	ED37	E39	400	36000	15000hrs (13.7yrs)		M59/E (ENCLOSED)