SALE on SATCO @ www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

SATCO' NUVO

Project Name

Location

Prepared By



SATCO S11254

10A19/LED/RGB/TW/T20/SF

Notes

General	
	Active
Status	Active
Watts	10
Incandescent Equivalent	60
Volts	120V A19
Shape	Medium
Base ANSI Base	E26
Finish	White
CCT (Kelvin)	2700K-5000K
	Warm to Cool White/Color
Temperature	Changeable
CRI	90
Lumens	800
Beam Spread	220
Dimmable	Dimmable Only with Starfish App
Hours Rated	15000
Lamp Type	Туре А
Technology	LED
Smart Product Info	
IOT Enabled	Yes
Voice Assistants Supported	Siri; Alexa; Hey Google; SmartThings
Electrical	
Electrical Operating Frequency	60 Hz
	60 Hz
Operating Frequency Specifications	60 Hz Smart
Operating Frequency Specifications	
Operating Frequency Specifications Dimming Type	Smart
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature	Smart 0.7 -20C (-4F) to a maximum of +45C
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F)
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.)	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.)	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No 3 Year Limited - 3 hr per day
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No 3 Year Limited - 3 hr per day cULus
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No 3 Year Limited - 3 hr per day cULus Damp
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No 3 Year Limited - 3 hr per day cULus Damp Yes
Operating Frequency Specifications Dimming Type Power Factor Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID	Smart 0.7 -20C (-4F) to a maximum of +45C (+113F) 4.57 2.36 0.16 No 3 Year Limited - 3 hr per day cULus Damp Yes ESID-2368816

Copyright 2020 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>https://www.satco.com/</u>



SALE on SATCO @ www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

FCC Compliant

SDS Sheet

Yes LED_Lamp

For More Information Visit: <u>https://www.satco.com/</u>

