



Project Name

Location

Prepared By



Notes

[www] 02-27-2023 01:59:16

### General

Status	Active
Watts	15W
Fluorescent Equivalent	55W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	White
CCT (Kelvin)	3500K/4000K/5000K
Temperature	Neutral White to Natural Light
CRI	83
Lumens	2150L/2200L/2200L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Technology	LED

### Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

### Physical

MOL	47.78
MOD	1.00
Material	Glass / Plastic
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White

### Additional Information

Shatter-Proof Type	PET Coated
Warranty	5 Year Limited - T8 LED Bulbs

### Compliance

Safety Listing	cULus - Listed; cULus - Classified; cETLus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	S-X87CKG
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes



SALE on SATCO at [www.BulbAmerica.com](http://www.BulbAmerica.com)  
take additional 5% Off with coupon code 5PDF

---