SATCO NUVO Project Name Location Prepared By **SATCO S11952** 7T8/LED/18-865/BP

| Notes | | | |
|-------|--|--|--|
| Notes | | | |

| ith coupon code 5PDF | | | |
|-------------------------|---|--|--|
| General | | | |
| Status | Active | | |
| Watts | 7W | | |
| Incandescent Equivalent | 75W | | |
| Fluorescent Equivalent | 15W | | |
| Volts | 120V-277V | | |
| Ballast Type | Туре В | | |
| Shape | T8 | | |
| Base | Medium Bi Pin | | |
| ANSI Base | G13 | | |
| Nominal Length | 18.00 | | |
| Finish | Frost | | |
| CCT (Kelvin) | 6500 | | |
| Temperature | Daylight | | |
| CRI | 83 | | |
| Lumens | 770L | | |
| Beam Spread | 160 | | |
| Dimmable | Non-Dimmable | | |
| Hours Rated | 50000 | | |
| Lamp Type | Linear | | |
| Technology | LED | | |
| Electrical | | | |
| Ballasting Requirements | Ballast Bypass | | |
| Operating Frequency | 50/60 Hz | | |
| Power Factor | 0.9 | | |
| THD | 25% | | |
| Operating Temperature | -25C (-13F) to a maximum of +40C (+104F) | | |
| Physical | | | |
| MOL | 17.80 | | |
| MOD | 1.10 | | |
| Material | Glass; Plastic | | |
| Lens Finish | Frost | | |
| Lens Material | Glass | | |
| Housing Color | White | | |
| Weight (lb.) | 0.26 | | |
| Additional Information | | | |
| Shatter-Proof Type | PET Coated | | |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass | | |
| Compliance | | | |
| Safety Listing | cULus Classified; cRUus | | |
| Location Rating | Damp | | |
| Energy Star | No | | |
| California Status | Lawful for sale | | |
| RoHS Compliant | Yes | | |
| FCC Compliant | Yes | | |
| NSF Approved | ETL Sanitation listed (conforms to NSF) | | |

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







