Project Name Location Prepared By



10.5T8/LED/48-830/BP/USA

Notes

3 0 4 00 0000 40 0

Till Coupon code 3F Di	
General	
Status	Active
Watts	10.5W
Fluorescent Equivalent	30W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	82
Lumens	1700L
Beam Spread	210
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Operating Temperature	
Operating Temperature Physical	-20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL	-20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL MOD	-20C (-4F) to +45C (+113F) 47.78 1.00
Operating Temperature Physical MOL MOD Material	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic
Operating Temperature Physical MOL MOD Material Lens Finish	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified;
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp No
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp No Yes
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp No Yes PLDUPAOQ3XWY
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID CA T20 / T24 Rationale	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp No Yes PLDUPAOQ3XWY Exempt - Base Not Regulated
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Specification Note Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID CA T20 / T24 Rationale California Status	-20C (-4F) to +45C (+113F) 47.78 1.00 Glass / Plastic Frost Glass White 0.44 Compatible with \$8000 and \$8002 LED EM Driver Yes 5 Year Limited - T8 LED Bulbs ULus - Classified; ULus - Certified; cRUus - Recognized Component Damp No Yes PLDUPAOQ3XWY Exempt - Base Not Regulated Lawful for sale in California

SALE on SATCO at www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







