SATCO | NUVO

Project Name

Location | Prepared By

SATCO S13143

80W/LED/HID/CCT/EX39/100-277V

Notes

General

Status	Active
Watts	80W
Incandescent Equivalent	400W
HID Equivalent	250W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	10400L-11200L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Technology	LED
Min Compartment Size	Length: 9.85 in. Width: 9.85 in. Depth: 10.95 in.

Electrical

Operating Frequency	50/60 Hz
Power Factor	0.9
Burning Position	Up or Down Operation Only
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

Physical

MOL	10.24
MOD	5.16
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Housing Color	White/Grey
Photocell	Yes
Weight (lb.)	3.30

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	This is not to be used with a ballast
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLQZVG5NED5L; PLLUNA05S0R
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes

SDS Sheet   LED_Lamp

For More Information Visit:
http://www.satco.com/