Project Name Location Prepared By



Ν	ot	е	s
-	_	_	_

30T8/LED/HO-SIGN/72-865/BP

[uama] 03_92_9091 0A-50-5

General	
Status	Active
Watts	30
Fluorescent Equivalent	87
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	72
Finish	Frosted
CCT (Kelvin)	6500
Temperature	Daylight
CRI	83
Lumens	4100
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

Physical	
MOL	69.88
MOD	1
Material	Plastic

Additional Information		
Installation Notes	No ballast or external driver required; Direct wire 120-277V line voltage; Single ended wiring	
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Sign	
Compliance		
Safety Listing	cULus Classified	
Location Rating	Damp	
Energy Star	No	
California Status	Lawful for sale in California	
Nevada Status	Lawful for sale in Nevada	
RoHS Compliant	Yes	

NSF Approved





Yes - Approved













