SALE on SATCO at www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

Project Name Location Prepared By



Notes			
110103			

www] 10-11-2023 00:58:4

Status	Active
Vatts	12W
ncandescent Equivalent	50W
luorescent Equivalent	45W
/olts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Recessed Double Contact HO/VHO
NSI Base	R17d
ominal Length	36
inish	White
CT (Kelvin)	4000K/5000K/6500K
emperature	Cool White to Daylight
RI	83
umens	1650L/1750L/1600L
eam Spread	360
Dimmable	Non-Dimmable
lours Rated	50000
amp Type	Linear
echnology	LED
Electrical	
allasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	33.81
MOD	1.13
Material	Polycarbonate (PC)
Lens Finish	Frost
Lens Material	Plastic
Weight (lb.)	0.47

Additional Information		
Tube Guard Use	No	
Rated For Enclosed Fixture	Yes	
Warranty	5 Year Limited - T8 LED Bulbs	

Compliance	
Safety Listing	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale

SALE on SATCO at www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	ETL Sanitation listed (conforms to NSF)	
SDS Sheet	LED Lamp	

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit:







