SATCO NUVO

Project Name

Location

Prepared By



SATCO S39679

90W/LED/HID/MB-G3/50K/100-277V

Notes

[uanai] 07-20-2020 00-51-24

Status	Active
Watts	90
Incandescent Equivalent	750
Fluorescent Equivalent	150
HID Equivalent	600
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	12600
Beam Spread	120;150;260
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	LED HID
Technology	LED
Min Compartment Size	Width 9.30 In. Depth 9.30 In Height 10.50 In.
Electrical	
Operating Frequency	50/60 Hz
Power Factor	>0.9

Electrical	
Operating Frequency	50/60 Hz
Power Factor	>0.9
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)

Physical	
MOL	9.84
MOD	4.84
Housing Color	White
Photocell	Optional Add-On
Weight (lb.)	3.48

Weight (ib.)	3.40
Additional Information	
Additional Info	PIR Sensor available as an accessory
Enclosure Rating	Enclosed Rated Lamp
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Closed 260 deg; Partial 150 deg; Open 120 deg
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus Classified
Location Rating	Damp









SALE on SATCO @ www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

Energy Star	No	
CEC Status	Lawful for sale in California	
RoHS Compliant	Yes	
SDS Sheet	LED Lamp	





