SATCO NUVO

Project Name

Location

Prepared By



60W/LED/HID/MB-G3/50K/100-277V

www] 07-20-2020 00:51:24

9
'-277V
cob
ıl Extended
)
ral Light
-
150;260
Dimmable
0
LUD
HID
ніи
9.30 In. Depth 9.30 In. nt 9.80 In.
9.30 In. Depth 9.30 In.
9.30 In. Depth 9.30 In.
n 9.30 In. Depth 9.30 In. nt 9.80 In.
n 9.30 In. Depth 9.30 In. nt 9.80 In.
n 9.30 In. Depth 9.30 In. nt 9.80 In. D Hz
n 9.30 In. Depth 9.30 In. nt 9.80 In. O Hz in surge protection - 4KV
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C
in 9.30 In. Depth 9.30 In. int 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C OF)
in 9.30 In. Depth 9.30 In. int 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C OF)
in 9.30 In. Depth 9.30 In. int 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C OF)
in 9.30 In. Depth 9.30 In. int 9.80 In. O Hz in surge protection - 4KV (-4F) to a maximum of +65C OF)
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz In surge protection - 4KV (-4F) to a maximum of +65C OF) In all Add-On Gensor available as an
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz In surge protection - 4KV (6 (-4F) to a maximum of +65C OF) Sensor available as an assory
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz In surge protection - 4KV (6 (-4F) to a maximum of +65C OF) Sensor available as an assory
in 9.30 In. Depth 9.30 In. in 9.80 In. O Hz In surge protection - 4KV (6 (-4F) to a maximum of +65C OF) Sensor available as an assory
r



Compliance
Safety Listing

Location Rating



Damp



cULus Classified





SALE on SATCO @ www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

Energy Star	No Lawful for sale in California	
CEC Status		
RoHS Compliant	Yes	
SDS Sheet	LED Lamp	





