



Project Name

Location

Prepared By



SATCO S8893

13T8/LED/48-850/DUAL/BP-DR

Notes

[www] 03-15-2021 00:27:54

General

Status	Active
Watts	13
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	83
Lumens	1900
Beam Spread	240
Dimmable	Non-Dimmable in Bypass Mode
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.96
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	48
MOD	1
Material	Glass
Housing Color	White

Additional Information

Additional Info	Do not use with dimmers in by-pass mode. Check the ballast for dimming capability when using with a ballast.
Shatter-Proof Type	PET Coated
Specification Note	Ballast Compatible - bare lamp is 12W; Ballast Bypass - 13W.; Protection from arcing- Power must be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracked or electrically compromised. If arcing occurs at the lamp pin, thermal fuse may activate to avoid overheating of lamp.
Warranty	5 Year Limited - T8 LED Bulbs

Compliance

cULus Listed for Type A; cULus



SALE on SATCO @ www.BulbAmerica.com
take additional 5% Off with coupon code 5PDF

Safety Listing	Classified for Type B
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLNHA25J4BZQ
California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
NSF Approved	Yes - Approved

