Product datasheet



GFT60DL/2G11/SE/OF



Product features and benefits

- Effective and environment-friendly disinfection without chemicals
- High UV-C radiance at 254 nm
- Low mercury content
- Long lifetime due to special coating
- Ozone-free

Areas of application

- Air
- Water Purification
- Surface Sterilization

Product datasheet

Technical data

General product information

Product Number	23402		
Product Name	GFT60DL2G11SEOF 10/CS 1/SKU		
Ordering Abbreviation	GFT60DL/2G11/SE/OF		
Brand Name	OSRAM		
Family Brand Name	Puritec		
General Description	60 watts, tube diameter 17.5mm,Germicidal ultraviolet (UVC) lamp with2G11 base. Primary emmision 253.7 nm, Ozone free		
Application	Air and water purification, surface disinfection		

Electrical data

Nominal Wattage	6000 W
Nominal Voltage	8200 V
Current (A)	0.80 A

Light technical data

Average Rated Life	8.000 h

Physical attributes

Base	2G11
Bulb Shape	T17,5
Length I (mm)	415 mm
Diameter d (mm)	40 mm
Distance a (mm)	380 mm

Additional product data

Safety advice

To prevent possible serious injury, eyes and skin should not be exposed to direct or reflected ultraviolet light emitted by this lamp. This lamp is in Risk Group 3 per ANSI/IESNARP-27.3-96. Adequate protection should be provided by clothing, gloves, opaque materials, and ordinary window glass. Although this lamp will operate in standard fluorescent fixtures, it should not be used for general lighting applications.

Packaging Information

SALE on Osram PURITEC HNS Compact L at www.BulbAmerica.com take additional 5% Off with coupon code 5PDF

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
23402	4052899012462	Folding box (SKU)	1	1.8 in x 1 in x 17.4 in	0.3 lb
23402	4052899012479	Shipping box (Case)	10	5.4 in x 4.1 in x 17.9 in	3.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.