





GE  
Lighting

### 41672 - FCWQ650PAR366

GE Quartzline® Showbiz® PAR36 - Stage & Studio



#### CAUTIONS & WARNINGS

##### Caution

- Risk of Burn
  - Allow lamp/fixture to cool before handling.
  - Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
  - Do not use lamp if outer glass is scratched or broken.
  - Dispose of lamp in a closed container.

##### Warning

- A damaged lamp emits UV radiation which may cause eye/skin injury
  - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
  - Avoid direct water/liquid contact.
  - Use in enclosed fixture rated for this product.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not exceed 110% of rated voltage.

#### GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR36
Base	Ferrule
Filament	C-7A
Rated Life	100.0 hrs
Primary Application	Stage & Studio

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	9000.0
Beam Spread - Horizontal	60.0 - 50.0 °
Beam Spread - Vertical	55.0 - 50.0 °
Center Beam Candlepower (CBCP)	9000.0
Color Temperature	3200.0 K
Max. Beam Candlepower (MBCP) (MAX)	9000.0
Nominal Initial Lumens per Watt	13

#### ELECTRICAL CHARACTERISTICS

Wattage	650.0
Voltage	120.0
Burn Position	Horizontal ±15°

#### DIMENSIONS

Maximum Overall Length (MOL)	2.7500 in(69.8 mm)
Bulb Diameter (DIA)	4.500 in(114.3 mm)

#### PRODUCT INFORMATION

Product Code	41672
Description	FCWQ650PAR366
ANSI Code	FCW
Standard Package	Case
Standard Package GTIN	10043168416723
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168416726