



Product Number: 54261

Order Abbreviation: ESB 64250 HLX

General Description: 20 Watt, tungsten halogen, low voltage without reflector

Product Information

Abbrev. With Packaging Info.	ESB64250HLX 6V 40/CS 1/SKU
Application	Projector
Average Rated Life (hr)	100
Base	G4 Bipin
Bulb	T9
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3350
Diameter d (in)	0.354
Diameter d (mm)	9.00
Distance a (in)	0.761
Distance a (mm)	19.5
Family Brand Name	XENOPHOT® (HLX)
Filament Dimensions Length (in)	0.031
Filament Dimensions Length (mm)	0.8
Filament Dimensions Width (in)	0.090
Filament Dimensions Width (mm)	2.3
Lamp Finish	Clear
Length l (in)	1.209
Length l (mm)	31
LIF Code	M/30
Light Center Length - LCL (in)	0.761
Light Center Length - LCL (mm)	19.5
Luminous Flux (lm)	460
Maximum Overall Length - MOL (in)	1.209
Maximum Overall Length - MOL (mm)	31
Nominal Voltage (V)	6.00
Nominal Wattage (W)	20.00
Operating Position	Any

Reflector Coating
Type of Current

9.00
AC