



Product Number: 54311

Order Abbreviation: HSD 150W/70 4ARXS

General Description: 150 watt, metal halide, single-ended, with outer jacket, non hot restart, 4ARXS HSD lamp series

Product Information

Abbrev. With Packaging Info.	HSD150W704ARXS 10/CS 1/SKU
Application	Effect and Architectural Lighting
Average Rated Life (hr)	3000
Base	G12
Bulb	SINGLE END
Class	C (gas)
Color Rendering Index (CRI)	85
Color Temperature (K)	7000
Cooling	Convection
Current (A)	1.8
Diameter d (in)	0.787
Diameter d (mm)	20.00
Distance a (mm)	56
Electrode Gap (cold) (mm)	5.5
Family Brand Name	4ArXS HSD®
Hot Restart	No
Lamp Finish	Clear
Length l (mm)	105
Length l max. (mm)	105
Light Center Length - LCL (mm)	56
Luminous Flux (lm)	12000
Maximum Base Temperature °C	450
Maximum Overall Length - MOL (mm)	105
Nominal Voltage (V)	92.50
Nominal Wattage (W)	150.00
Operating Position	Any
Reflector Coating	20.00

Type of Current

AC



Footnotes

- Type of current: sine-wave (sinusoidal) AC.
- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.