



Product Number: 54321

Order Abbreviation: HMI 4000W/SE/XS

General Description: 4,000 watt, metal halide, single-ended, 6000K

Product Information

Abbrev. With Packaging Info.	HMI4000WSEXS 1/CS 1/SKU
Application	Film, TV & Video Production. Studio Ltg
Average Rated Life (hr)	500
Base	G38 Mogul Bipost
Bulb	GST75
Class	C (gas)
Color Rendering Index (CRI)	90
Color Temperature (K)	6000
Cooling	Convection
Current (A)	24.0
Diameter d (in)	2.953
Diameter d (mm)	75.00
Distance a (mm)	142
Electrode Gap (cold) (mm)	20
Family Brand Name	HMI®
Hot Restart	Yes
Lamp Finish	Clear
Length l (mm)	250
Length l max. (mm)	250
Light Center Length - LCL (mm)	142
Luminous Efficacy (lm/W)	95
Luminous Flux (lm)	380
Maximum Base Temperature °C	450
Maximum Overall Length - MOL (mm)	250
Nominal Voltage (V)	200.00
Nominal Wattage (W)	4000.00
Operating Position	Any
Reflector Coating	75.00

Type of Current

AC

Footnotes

- Type of current: sine-wave (sinusoidal) AC.
- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.