



Product Number: 54354

Order Abbreviation: 64514

General Description: 300 WATT, TUNGSTEN HALOGEN, MEDIUM TO HIGH VOLT, SINGLE-ENDED

Product Information

Abbrev. With Packaging Info.	64514 120V 12/CS 1/SKU
Application	Projector, Stage & Studio
Average Rated Life (hr)	75
Base	GX6.35 Bipin
Bulb	T6
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3400
Diameter d (in)	0.728
Diameter d (mm)	18.50
Distance a (in)	1.053
Distance a (mm)	27
Filament Dimensions Length (in)	0.492
Filament Dimensions Length (mm)	12.5
Filament Dimensions Width (in)	0.406
Filament Dimensions Width (mm)	10.3
Lamp Finish	Clear
Length l (in)	2.086
Length l (mm)	53
Length l max. (in)	2.086
Length l max. (mm)	53
LIF Code	CP/96
Light Center Length - LCL (in)	1.053
Light Center Length - LCL (mm)	27
Luminous Flux (lm)	8100
Maximum Overall Length - MOL (in)	2.086
Maximum Overall Length - MOL (mm)	53
Nominal Voltage (V)	120.00

Nominal Wattage (W)	300.00
Operating Position	s 90
Reflector Coating	18.50
Type of Current	AC

Footnotes

- s (Operating Position) = Vertical, base down
- For use where seal temperature does not exceed 650F.
- Life at rated voltage and at 650F maximum seal temperature.