5% OFF All GREENLUX www.BulbAmerica.com

with coupon code 5PDF




DL Series Retrofit Downlight 5&6 inch LED Downlight


IMPORTANT SAFEGUARDS

WARNING-Risk of fire or electric shock. Disconnect power at fuse or circuit breaker before installing or servicing.

READ AND FOLLOW ALL SAFETY INSTRUCTIONS

- 1. WARNING Risk of fire or electric shock. LED Retrofit Kit installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation. Contact a qualified electrician.
- 2.WARNING Risk of fire or electric shock. Install this kit only in luminaires that have the construction features and dimensions shown in the photographs and/or drawings and where the input rating of the retrofit kit does not exceed the input rating of the luminaire.
- 3. WARNING To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.
- 4.It may be necessary to remove a socket mounting plate for adequate clearance.
- 5.Each downlight shall be installed only in its intended manner and orientation.
- 6.Suitable for Damp Locations.
- 7.Min. temperature rating of -25 °C.
- 8.Do not make or alter any open holes in an enclosure of wiring or electrical components during kit installation.






TO INSTALL:


STEP 1:

Make sure the **power is turned off** at the source to the recessed can.


STEP 2:

This retrofit downlight was set for 6 inch fixture housing. (See image1). When need to be fitted to 5 inch fixture housing,lossen the two screws with the cross screw driver, slide the hook towards position "5". Then tighten screw. (See image2).





E28 Adapter's male connector Downlight's female connector



STEP 3:

Srew the E26 socket adapter into recessed can socket by turning clockwise.(see image3).

STEP 4:

Plug E26 adpater's male connector to the downlight's femal connector. (See image4).

STEP 5:

Push two ends of the Flip Clip toward each other till it can fit into the recessed can(see image5).

STEP 6:

Install the downlight up into resecced can firmly until the rim ring is flush with the ceiling(see image6).

LEDUX LED INC 715W 31ST ST UNIT 1 SAN PEDRO, CA 90731 Tel:1-800-604-1913 E-mail: ledux@ledux-lighting.com http://www.ledux-lighting.com