

* Cable and mounting pole not included

Laird Connectivity premium series directional Yagi antennas are either fully gold anodized or black powdercoat for corrosion resistance. These antennas feature internal matching to assure broad bandwidth and resistance to severe weather conditions. There is no gamma match to ice up, corrode, or detune. Our engineering staff optimized this product family for forward gain by computer analysis and then field-tested each for conformance.

FEATURES AND BENEFITS

- These antennas feature 360° welds around each element and an end-of-boom N connector feed with an internal transmission line feeding the driven element.
- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR.
- All Yagi antennas ship complete with a high-quality cast aluminum mounting kit that includes stainless steel hardware and allows vertical or horizontal orientation during installation

APPLICATIONS

- Point-to-point and multi-point/omnidirectional outdoor antenna applications used by private organizations and governments worldwide
- Transportation such as railroad switching
- Remote locations such as oil fields
- Weather conditions
- Meter data transmissions for utilities

ELECTRICAL SPECIFICATIONS

Model Name	Y(B)8966
Operating Frequency (MHz)	896-970
VSWR	<2:1
Nominal Gain (dBd)	9
Front-to-Back Ratio (dBd)	20
Max Power - Ambient 25°C (W)	300
Nominal Impedance (Ohms)	50
Polarization	Vertical or horizontal
Pattern	Directional
Horizontal Plane 3 dB Beamwidth	56°
Vertical Plane 3 dB Beamwidth	52°
Tuning	Fixed
Transmitting/Receiving	Both
Gamma Match Type	Internally Matched

MECHANICAL SPECIFICATIONS


Dimensions – L x H – cm (inches)	70.33 x 17.15 (27.69 x 6.75)
Boom Diameter – cm (inches)	26.68 (0.875)
Weight – kg (lbs.)	1.77 (3.9)
Cable Type	None
Connector	N-female
Color	Gold or black
Lightning Protection	Lightning arrestor (LABH350NN – sold separately)
Element Construction	Welded
Mounting (included)	Heavy duty cast aluminum bracket accommodates up to 2 ½" mast

ENVIRONMENTAL SPECIFICATIONS


Rated Wind Velocity – km/hr (mph)	241 (150)
Rated Wind Velocity (w/ 0.5" radial ice) – km/hr (mph)	130 (80)
Equivalent Flat Area – sq. km (sq. ft.)	2.3151 (0.2492)

CONFIGURATION

PART NUMBER	FREQUENCY RANGE	COLOR
Y8966	896-970 MHz	Gold
YB8966	896-970 MHz	Black



Vertical-to-Vertical Polarization
Azimuthal Pattern
(Y, Z, or E-plane)



Horizontal-to-Horizontal Polarization
Azimuthal Pattern
(Y, Z, or H-plane)



Laird Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird Connectivity product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials rests with the end user, since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to the fitness, merchantability or suitability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity shall not be liable for incidental or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2021 Laird Connectivity All Rights Reserved. Laird Connectivity, the Laird Connectivity logo, and other marks are trademarks or registered trademarks of Laird Connectivity or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Connectivity or any third-party intellectual property rights.

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com

