



EXC400

Today's work and lifestyles require us to communicate anytime, anywhere whether on the move or sitting still. Bluetooth and 802.11 standards make wireless connections to computer networks and other devices possible, while at the same time enabling freedom of movement.

Laird Technologies' practical and rugged external wireless device antennas are designed to fit into the portable devices used in office, industrial and home environments. The antennas feature flexible elements and many are 1/2 wave coaxial dipole design for reduced ground dependence and improved performance.

FEATURES

- Injection molded 1/4 wave flexible cable antenna
- High durability, high efficiency
- Textured finish with strain-relief base
- Available in various standard connectors
- An original 'Tuf Duck' antenna

MARKETS

- For Bluetooth & IEEE 802.11b/g devices

PARAMETER	SPECIFICATION
Frequency Range	UHF Trunking/Cellular
VSWR	1.5:1 max at resonance
Polarization	Vertical
Nominal Impedance	50 ohms
Temperature Range	-40°C to +85°C
Power Rating	50 Watts
Drop Test	1 M

The EXC model antenna is available in the following frequencies and connectors.

Order by antenna model, frequency and connector. For example: EXC450MX.

Length of each antenna will vary according to the connector chosen.

PART#	FREQUENCY BAND	CONNECTORS	AVERAGE LENGTH
EXC400	400-420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN & TNX	6.75" – 7.0"
EXC410		SMI	
EXC420	420-450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	6.75" – 7.0"
EXC440		SMI	
EXC450	450-470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN & TNX	6.39" – 6.9"
EXC470	470-512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN & TNX	6.13" – 6.7"
EXC806	806-866 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	3.7" – 4.6"
EXC902	902-960 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	3.5" – 3.65"

Specifications subject to change without notice according to the connector chosen.

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-EXC400 0609

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2009 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.