

## Hornet LED Floodlight

The Hornet LED floodlight is designed to be discrete with its compact, slimline design. With an adjustable head and flexible rotation, the Hornet can be installed under eaves to light BBQ areas, outdoor entertaining areas and access areas without being obtrusive.

Now available in warm white (3000K).

- Adjustable head 300° horizontal, 200° vertical with flexibility to direct the light (up/down/sideways)
- Slim and compact, designed to disappear when mounted under the eave
- Complete with 1m lead for easy installation



80

CRI



IP66

Ingress Protection Rating



7SDCM

MacAdam Steps



0°C to 40°C

Operating Temperature



Non - Dimmable

Dimming



30,000hrs (L70/B50)

Lifetime



3 Years

Warranty



Symmetric

Beam Distribution




120°


Beam Angle

CODE	LAMP POWER	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS
CFL20830	20W	20W	1560lm	80lm/W	3000K	L186 x W125 x H23 mm
CFL20840	20W	20W	1600lm	80lm/W	4000K	L187 x W125 x H23 mm

### Line Drawings



CFL20840



Maximum Candela = 1298.097 Located At Horizontal Angle = 0, Vertical Angle = 0  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd)  
# 2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd)

Product Images

