



ASSEMBLY GUIDE



VILLA SOFA SEATS

The seat part comes made up and is numbered on the side. The leg assembly must have a matching number on the box. Each set has five bolts either side on each side. The longer bolts attach through the armrest to the back of the seat and the remaining bolts attach the legs to the base of the seat.

Put all five bolts through the leg/arm assembly first and offer up to the seat knocking the bolts in a little at a time in rotation. It may help to clean all threads after they have been knocked through the predrilled holes before fitting your nuts and washers.

The “FLIP LEG” should now be fitted to the assembled chair. Bolt the two leg extensions to the inside of the back legs using the two bolts provided and the Butterfly nuts (these nuts are threaded on the inside face of each leg).

Now attach the flat cross support using the four screws provided (bradawl marks show the position) so it is on to the front side of the back legs. Do not fit the screws too quickly as they may overheat and shear.

This therefore acts as a stop when the legs are down for the eating position and swings up and under the seat base when in the relaxed sitting position. (See photo in brochure for extra help).



DON'T FORGET TO PAINT ON THE FURNITURE PROTECTOR AS SOON AS THE PRODUCT IS ASSEMBLED, UNLESS ANOTHER FINISH IS TO BE APPLIED.



Sustainably
Sourced &
Ergonomically
Designed

www.pepegarden.co.uk

