

Multi-Purpose Compounds

4TBX 4TBKT





AVAILABLE IN WHITE & TINTED

SUITS TAPING, SECOND COAT, TOP COAT & TEXTURING

HIGH QUALITY & EXCELLENT SMOOTH FINISH

WHAT IS IT?

4T is a pre mixed light weight all purpose compound with a variety of uses such as taping, second coat and texturing

WHEN TO USE IT?

Recommended for all applications associated with setting plasterboard joints, metal and PVC externals and Internal angles. Can also be used for texture coating plasterboard.

QUICK _		TIBICI
FACTS	Category:	Multi-purpose/Top coat
	Shrinkage:	Low
Taping:		Excellent
2nd & Finishing Coats:		Excellent
Fastener Cover:		Excellent
Metal Bead Cover:		Excellent
Sanding:		180-220
Colour:		White, Tinted
Packaging:		Bucket / Refill Carton
Bucket Weight:		15 Litres
Carton Weight:		13.8 Litres
Best By Date:		12 months from manufacturing date, if stored correctly

Packaging/Colour:	WHITE	TINTED
Bucket	4TBKT-W	4TBKT-T
Carton	4TBX-W	4TBX-T

Job conditions:	Require minimum temperature 10°C to be maintained 48 hours prior to application and until "dry" and stable. Maintain minimum air, joint compound and surface temperature of 13°C within working area until joints are completely dry.
Ideal tool usage:	Automatic & Hand Tools
Setting time:	Air Drying, allow to dry thoroughly between coats (can be up to 24 hours depending on climatic conditions)
Mixing / Dilution:	Thinning is not normally required, if needed add minimal water while mixing.
Product Hints:	Always use clean tools to stop the likelihood of product contamination. Never use base cements as a second coat over a Multi-Purpose First coat. Not suitable for taping fibre cement sheeting. Note: Humidity can effect drying time.
Product Warranty:	Pro Plaster Products guarantee its products to be free of defects in materials and manufacture. If a Pro Plaster Product does not meet our standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these, this warranty is supported by Pro Plaster Products.
Relevant Standard Compliance:	Meet or exceed ATSM C-475 "Standard specification for Jointing Compound and Joint Tape for Finishing Gypsum Plasterboard"
Alternative Products:	Pro Top, Hamilton All Purpose

Your one stop shop for COMPOUNDS | TOOLS | ACCESSORIES