



HIGH HIDING POWER

MINIMISES JOINT BANDING

SANDABLE

WHAT IS IT?

Flaw Hide is a high performance low VOC basecoat designed to create a uniform surface on internal plasterboard and Fibre Cement wall and ceiling linings in preparation for high quality Level 5 finishing. The use of this product will not automatically upgrade a job to a level 5 finish. A Level 5 Finish needs to be performed by following the relevant standard: AS/NZS 2589

WHEN TO USE IT?

Pre-treatment of internal linings where a superior smooth or gloss finish is expected.

QUICK FACTS

Category:	Water-based acrylic compound
Shrinkage:	Not Applicable
Application:	Roll or airless spray*
Sanding:	180-240 grit
Colour:	White
Packaging:	15 Litre

Job conditions:	Optimum application temperature is 10°C to 35°C. High humidity and severe temperatures will affect drying and recoat times.
Setting Time:	Air Drying, allow to dry thoroughly for 16-24 hours or longer under adverse conditions.
Mixing / Dilution:	Thinning is not recommended. Clean equipment with fresh water.
Product Hints:	Stir thoroughly before and during application. Apply by 10-12mm microfibre paint roller or airless spray using an 519 to 621 tip. This product does not negate the need of primer/undercoats.
Product Warranty:	Pro Plaster Products guarantee its products to be free of defects in materials and manufacture. Should a Pro Plaster Product fail to meet our high standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these, this warranty is supported by Pro Plaster Products.
Relevant Standard Compliance:	Meet or exceed Australian Standard AS/NZS 2589.
Alternative Products:	Not Applicable
Special notes:	*This is a paint product, not a plastering compound. Flaw Hide should be professionally applied, preferably by airless spray to achieve a superior finish.