



REPAIRS CRACKS & HOLES

PROFESSIONAL LIGHTWEIGHT FORMULA

QUICK DRYING, SMOOTH & NON-SHRINKING

WHAT IS IT?

Hamilton EZ Patch is a pre mixed light weight patching compound that is ideal for patching and fixing minor damages on plasterboard.

WHEN TO USE IT?

Hamilton EZ Patch can be used on any plasterboard in repairing cracks and holes.

QUICK FACTS	Category:	Multi-purpose/Top Coat
	Shrinkage:	Low
	Taping:	Excellent
	2nd & Finishing Coats:	Excellent
	Fastener Cover:	Excellent
	Metal Bead Cover:	Excellent
	Sanding:	Easy - 220# mesh
	Colour:	White
	Packaging:	0.83L Pail / 3.3L Pail

Job conditions:	Require minimum temperature 10°C to be maintained 48 hours prior to application and until "dry" and stable. Maintain minimum air, joint compound and surface temperature of 13°C within working area until joints are completely dry.
Setting Time:	Air Drying, allow to dry thoroughly between coats (can be up to 24 hours depending on climatic conditions)
Mixing / Dilution:	Thinning is not normally required, if needed add minimal water while mixing.
Product Hints:	<p>Always use clean tools to stop the likelihood of product contamination.</p> <p>Never use base cements as a second coat over a Multi-Purpose First coat.</p> <p>Not suitable for taping fibre cement sheeting. Note: Humidity can effect drying time.</p>
Product Warranty:	Hamilton Products guarantee its products to be free of defects in materials and manufacture. If a Hamilton Products product does not meet our standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these, this warranty is supported by Pro Plaster Products.
Relevant Standard Compliance:	Meet or exceed ATSM C-475 "Standard specification for Jointing Compound and Joint Tape for Finishing Gypsum Plasterboard"
Alternative Products:	4T Multi-Purpose DIY, Hamilton FastSet