



SUITS TAPING, SECOND COAT & TOP COAT

HIGH QUALITY FINISH

DRIES HARDER & STILL EASY TO SAND

WHAT IS IT?

Hamilton All Purpose is a pre-mixed light weight all purpose compound formulated in the USA especially for Australian standards. Consistent quality guarantees the plasterer excellent workability to finish the job with ease providing the highest quality finish.

WHEN TO USE IT?

Recommended for all applications associated with setting plasterboard joints, metal and PVC externals and Internal angles.

QUICK FACTS

Category:	Multi-purpose/Top coat
Shrinkage:	Low
Taping:	Excellent
2nd & Finishing Coats:	Good
Fastener Cover:	Good
Metal Bead Cover:	Excellent
Sanding:	180-220
Packaging:	Bucket / Refill Carton

Job conditions:

Require minimum temperature 10°C to be maintained 48 hours prior to application and until "dry" and stable. Maintain minimum air, joint compound and surface temperature of 13°C within working area until joints are completely dry.

Ideal tool usage:

Automatic & Hand Tools

Setting Time:

Air Drying, allow to dry thoroughly between coats (can be up to 24 hours depending on climatic conditions)

Mixing / Dilution:

Thinning is not normally required, if needed add minimal water while mixing.

Product Hints:

Always use clean tools to stop the likelihood of product contamination. Never use base cements as a second coat over a Multi-Purpose First coat.

Not suitable for taping fibre cement sheeting. Note: Humidity can effect drying time.

Product Warranty:

Hamilton guarantee its products to be free of defects in materials and manufacture. If a Solid Products product does not meet our standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these, this warranty is supported by Pro Plaster Products.

Relevant Standard Compliance:

Meet or exceed ATSM C-475 "Standard specification for Jointing Compound and Joint Tape for Finishing Gypsum Plasterboard"

Alternative Products:

Pro Top, 4T Multi-Purpose