



LIGHTWEIGHT PREMIUM SETTING

SUITS TAPING, SECOND COAT & TOP COAT

AVAILABLE IN 5 OR 20 MINUTES SET TIME

WHAT IS IT?

Hamilton Fast Set is a chemical setting compound that is ideal for patching and fixing minor damages on plasterboard

WHEN TO USE IT?

Hamilton Fast Set can be used on any plasterboard in repairing cracks and holes

QUICK FACTS

Category:	Base and Bedding
Shrinkage:	Low
Taping:	Excellent
2nd & Finishing Coats:	Not Recommended for finishing coat
Fastener Cover:	Excellent
Metal Bead Cover:	Excellent
Sanding:	Easy - 180 -220 grit
Colour:	White
Packaging:	2KG Refill Carton

Job conditions: Minimum temperature of 8°C to be maintained 24 hours prior to application and until "dry" and stable.

Setting Time: Air Drying, allow to dry thoroughly between coats (can be up to 24 hours depending on climatic conditions)

Mixing / Dilution: Can be hand mixed or chemically mixed at low speed

Product Hints: Always use clean tools to stop the likelihood of product contamination. Never use base cements as a second coat over a Multi-Purpose First coat.

Not suitable for taping fibre cement sheeting. Note: Humidity can effect drying time.

Product Warranty: Hamilton Products guarantee its products to be free of defects in materials and manufacture. If a Hamilton Products product does not meet our standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these, this warranty is supported by Pro Plaster Products.

Relevant Standard Compliance: Meet or exceed ATSM C-475 "Standard specification for Jointing Compound and Joint Tape for Finishing Gypsum Plasterboard"

Alternative Products: 4T Multi-Purpose DIY, FastSet