

Pro Base Cement

PB40 PB60 PB90





MIXES & TROWELS EASILY

STRONG ADHESION & BONDING QUALITIES
SMOOTH CREAMY CONSISTENCY

WHAT IS IT?

Pro Plaster Products Exclusive, the Pro Base is a powder base cement formulated to suit Australian conditions.

WHEN TO USE IT?

Pro Base can be used for taping and second coating plasterboard joints. Can also be used for coating metal, PVC angles and covering fasteners.

QUICK	Catanama	PB90
FACTS	Category:	Bedding and Base
Shrinkage:		Low
Taping:		Excellent
2nd & Finishing Coats:		Excellent for 2nd Coat.
Fastener Cover:		Excellent
		Not Recommended for finish coat
Metal Bead Cover:		Excellent
Sanding:		Not Applicable
Packaging:		20kg Bag

Job conditions:	Should be clean and dry with adequate ventilation to enhance drying, if conditions are too hot with dry winds this will affect the setting and strength of the product.	
Ideal tool usage:	Automatic & Hand Tools	
Setting Time:	PB40 - Sets in 35-45 minutes PB60 - Sets in 65-80 minutes PB90 - Sets in 90-105 minutes	
Mixing / Dilution:	Mix with water to produce the required consistency	
Product Hints:	Always use clean tools to stop the likelihood of product contamination. Always use clean water. Allow to dry thoroughly before applying the next coat. Can be used to tape and second coat internal fibre cement sheeting joints & angles. Not suitable as a second coat over ready mixed taping products or all/multi-purpose products. Note: Weather conditions can affect drying time	
Product Warranty:	Pro Plaster Products guarantee its products to be free of defects in materials and manufacture. If a Pro Plaster Products product does not meet our standard, we will at our option, replace or repair it, supply an equivalent product, or pay for doing one of these.	
Relevant Standard Compliance:	Meet or exceed ISO 9002 Quality Management System	
Alternative Products:	Trade Base Cement	

Your one stop shop for COMPOUNDS | TOOLS | ACCESSORIES