



TINTED

**SUITS SECOND COAT,
TOP COAT & TEXTURING**

HIGH QUALITY & EXCELLENT SMOOTH FINISH

WHAT IS IT?

Pro Lite Lightweight Topping Compound is designed for the professional. It is an ultra-premium air-dry finishing compound developed for superior coverage, easy application and sandability.

WHEN TO USE IT?

It is highly recommended as finish coat and can be applied by mechanical or hand application over joints, angles and fastener heads.

QUICK FACTS

Category:	Top coat
Shrinkage:	Low
Taping:	N/A
2nd & Finishing Coats:	Excellent
Fastener Cover:	Excellent
Metal Bead Cover:	Excellent
Sanding:	180-220
Colour:	Tinted
Packaging:	Bucket /Carton

Job conditions:	Require minimum temperature above 10°C to be maintained 48 hours prior to application and until "dry" and stable. Maintain minimum air, joint compound and surface temperature of above 10°C within working area until joints are completely dry.
Ideal tool usage:	Automatic & Hand Tools
Job Conditions	Air drying, allow to dry thoroughly between coats (can be up to 24 hours depending on climatic conditions)
Mixing / Dilution:	Thinning is not normally required, if needed add minimal water while mixing.
Product Hints:	Always use clean tools to stop the likelihood of product contamination. Humidity can effect drying time.
Product Warranty:	Pro Plaster Products warranties its products to be free of defects in materials and manufacture, complaint to the Plasterboard Australian Standard AS 2588. Pro Plaster guarantees its compounds on any brand of Plasterboard.
Relevant Standard Compliance:	Meet or exceed AS 2588
Alternative Products:	Pro Top