

TRADE BASE



EXCELLENT ADHESION & STRONG BONDING

**SUITS TAPING, SECOND COAT
& COATING METAL**

SMOOTH CREAMY CONSISTENCY

WHAT IS IT?

Pro Plaster Products Exclusive, the Trade Base is a power base cement manufactured in Australia and formulated to suit Australian conditions.

WHEN TO USE IT?

Trade Base can be used for taping and second coating plasterboard joints. Can also be used for coating metal, PVC angles and covering fasteners.

QUICK FACTS

Category:	Bedding and Base
Shrinkage:	Low
Taping:	Excellent
2nd & Finishing Coats:	Excellent for 2nd Coat. Not Recommended for finish coat
Fastener Cover:	Excellent
Metal Bead Cover:	Excellent
Sanding:	Not Applicable
Packaging:	20kg Bag

Job conditions: Should be clean and dry with adequate ventilation to enhance drying, if conditions are too hot with dry winds this will affect the setting and strength of the product.

Ideal tool usage: Automatic & Hand Tools

Setting Time: TB40-20 - Sets in 35-45 minutes
TB60-20 - Sets in 65-80 minutes

Mixing / Dilution: Mix with water to produce the required consistency

Product Hints: Always use clean tools to stop the likelihood of product contamination.
Always use clean water.
Allow to dry thoroughly before applying the next coat.
Can be used to tape and second coat internal fibre cement sheeting joints & angles.
Not suitable as a second coat over ready mixed taping products or all/multi-purpose products.
Note: Weather conditions can affect drying time

Product Warranty: Pro Plaster Products guarantees Trade Base to be used on any plasterboard surface when the manufactured plasterboard complies to Australian Standard AS 2588. In the event of any failure of the product caused by the direct result of a defect in the material or manufacture of the product, Pro Plaster Products will at its option replace or repair, supply an equivalent product, or pay for doing one of these.

Relevant Standard Compliance: Meet or exceed ISO 9002 Quality Management System

Alternative Products: Pro Base Cement