

RIVER QUIVER LOCK REPLACEMENT



INSTALLATION INSTRUCTIONS

WWW.RIVERSMITH.COM

@RIVERSMITHUSA



CONTENTS

- 1 INCLUDED PARTS & TOOLS NEEDED
- 2 STEP 1 - INSTALL THUMB CATCH ONTO TUMBLER
- 3 STEP 2 - INSERT TUMBLER INTO REEL BOX LID
- 4 STEP 3 - INSTALL WASHERS AND TUMBLER NUT
- 5 STEP 4 - CHECK ALIGNMENT, KEYS, AND LOCK

NOTE:

ALL DAMAGED LOCK PARTS MUST
BE REMOVED PRIOR TO INSTALLING
REPLACEMENT LOCK

INCLUDED PARTS

LOCK REPLACEMENT KIT



TOOLS NEEDED



CHANNEL LOCKS OR
LARGE PLIERS

PARTS

The SWIFTCAST Rod Holder is built and tested to the highest possible standards to securely transport and protect your gear, however it is not meant as a long term storage solution.

STEP 1

Install Thumb Catch onto Tumbler

1

Pre-assemble Thumb Catch onto the Tumbler. Ensure the catch is on the same side as the tumbler latch for proper installation.

THUMB
CATCH

TUMBLER

TUMBLER
LATCH

CATCH

THUMB CATCH +
TUMBLER
COMPLETE ASSEMBLY

STEP 2

Insert Tumbler (with Thumb Catch) into tumbler hole on the Reel Box Lid.

2

From the outside face of the Reel Box Lid, insert the Tumbler (with Thumb Catch installed) through the open tumbler hole. Quickly move to Steps 3-5 as the Tumbler is now loose and unsecured.



STEP 2

3

STEP 3

Install the Washers and Tumber Nut onto Tumbler

3

On the inside of the Reel Box Lid, first install the Alignment Washer. Then overtop the Alignment Washer, install the Tumbler Nut. Use a pair of channel locks or large pliers to securely tighten the Tumbler Nut.

- DO NOT OVERTIGHTEN OR DAMAGE

▲ WILL OCCUR



ALIGNMENT
WASHER



TUMBLER
NUT

STEP 4

Check alignment, keys, and lock.

4

With the Replacement Lock now installed, close the Reel Box Lid. Ensure the Lid closes tightly and the latch is secure. Now insert a key into the Tumbler and test the locking mechanism by pressing your thumb against the button lock. If secure, you are now LOCKED. LOADED. READY TO FISH.



ENSURE LID
CLOSES TIGHTLY



USE KEY TO CHECK
LOCK MECHANISM



ENSURE LOCK IS
WORKING

NOTE: **River Quiver must be locked in order to function properly.**

STEP 4

5

— RIVER QUIVER REPLACEMENT LOCK IS A PRODUCT BY —



LOCKED & LOADED LIMITED LIFETIME WARRANTY

Riversmith takes pride in the products we manufacture and will warrant that all Rod Holders will be free from defects in workmanship and materials for the life of the product to the original purchaser (“you”), subject to the below conditions:

- Replacement Lock was purchased from a Riversmith authorized dealer;
- You can provide proof of purchase from the Riversmith authorized dealer;
- The product was used only as intended and in accordance with the Replacement Lock installation guide.

If a defect occurs during intended use (according to the installation guide), we will replace, at our discretion, the defective product or part. The warranty does not cover defects caused by misuse, overloading, modifications, or improper assembly. Cosmetic damage, loss, theft, normal wear and tear, and the natural breakdown of colors and materials over time and use are not warranted. If damage is deemed outside of the scope of this warranty, replacement parts will be available at discounted prices.

Warranty Disclaimer:

UNDER NO CIRCUMSTANCES, WHETHER FOR BREACH OF WARRANTY, BREACH OF CONTRACT, NEGLIGENCE, OR OTHER TORT, OR ANY STRICT LIABILITY THEORY, WILL RIVERSMITH BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES TO NON-RIVER QUIVER PRODUCTS USED IN CONJUNCTION WITH RIVER QUIVER PRODUCTS.

The warranty is only available in the United States. No Riversmith reseller, agent, or employee is authorized to make any modification, extension, or addition to this warranty.