

Sponsor: Nitin Philip Case-Mate Inc. 7000 Central Pkwy. Atlanta, GA 30328

Bacterial Filtration Efficiency (BFE) Final Report

Test Article:	SAFE-MATE CLOTH MASK WITH FILT SAFE-MATE CLOTH MASK WITHOUT	
Study Number:	1304932-S01	
Study Received Date:	29 May 2020	
Testing Facility:	Nelson Laboratories, LLC	
	6280 S. Redwood Rd.	
	Salt Lake City, UT 84123 U.S.A.	
()	Standard Test Protocol (STP) Number: None	STP0004 Rev 18

Summary: The BFE test is performed to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts downstream. A suspension of *Staphylococcus aureus* was aerosolized using a nebulizer and delivered to the test article at a constant flow rate and fixed air pressure. The challenge delivery was maintained at $1.7 - 3.0 \times 10^3$ colony forming units (CFU) with a mean particle size (MPS) of $3.0 \pm 0.3 \mu m$. The aerosols were drawn through a six-stage, viable particle, Andersen sampler for collection. This test method complies with ASTM F2101-19 and EN 14683:2019, Annex B.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.

Test Side:	Inside
BFE Test Area:	~7.1 cm ²
BFE Flow Rate:	28.3 Liters per minute (L/min)
Conditioning Parameters:	85 \pm 5% relative humidity (RH) and 21 \pm 5°C for a minimum of 4 hours
Test Article Dimensions:	~220 mm x ~171 mm (SMCM-F); ~230 mm x 171 mm (SMCM-NF)
Positive Control Average:	2.3 x 10 ³ CFU
Negative Monitor Count:	<1 CFU
MPS:	2.7 μm



Trang Truong electronically approved for

Study Director

James Luskin

07 Jul 2020 23:37 (+00:00) Study Completion Date and Time

kxh



Results:

SAFE-MATE CLOTH MASK WITH FILTER / SMCM-F:

Test Article Number	Percent BFE (%)
1	97.4
2	95.5
3	97.3
4	96.3
5	98.3

SAFE-MATE CLOTH MASK WITHOUT FILTER / SMCM-NF:

Test Article Number	Percent BFE (%)
1	71
2	77
3	75
4	73
5	75

The filtration efficiency percentages were calculated using the following equation:

%
$$BFE = \frac{C-T}{C} \times 100$$

C = Positive control average
T = Plate count total recovered downstream of the test a
Note: The plate count total is available upon request

downstream of the test article