

Nylon Cable Glands (Metric) M type



Features:

The claws and seals of excellent design, sealing nut have a “click” sound and re-open, can hold cable firmly and have a wider cable range. Resistant to salt water weak acid, alcohol, oil grease and common solvency.

- UV stable
- Thread: Metric thread
- Materials:
 - UL approved Nylon PA66 (Flammability UL 94V-2) for A. C. F parts, (Accept to make flammability UL 94V-O); EPDM rubber for B. D parts, (Also accept to make super rubber-resist high-temperature rubber resist strong acid/alkali.etc).
- Protection degree: IP68
- Working temperature: -40°C to 1 00°C
- Colours:
 - Dark Grey(RAL7035), and Light Grey(RAL7001) and Black(RAL9005)

Metric Type IP 68 Polyamide Cable Gland (RAL 7035) Light Grey, (RAL 7001) Dark Grey & (RAL 9005) Black						
Product Code Dark Grey RAL 7035	Product Code Light Grey RAL 7001	Product Code Black RAL 9005	Size	Mounting Dia C	Cable Die Min-Max B	Thread Length D
M12x1.5LG	M12x1.5DG	-	M12 x 1.5	12	3-6.5	8
M16x1.5LG	M16x1.5DG	M16x1.5B	M16 x 1.5	16	5-10	8
M20x1.5LG	M20x1.5DG	M20x1.5B	M20 x 1.5	20	6-12	10
M25x1.5LG	M25x1.5DG	M25x1.5B	M25 x 1.5	25	13-18	10
M32x1.5LG	M32x1.5DG	M32x1.5B	M32 x 1.5	32	16-21	11
M40x1.5LG	M40x1.5DG	M40x1.5B	M40 x 1.5	40	22-32	14
M50X1.5LG	M50X1.5DG	M50X1.5B	M50 x 1.5	50	32-38	14
M63x1.5LG	M63x1.5DG	M63x1.5B	M63 x 1.5	63	37-44	15
M16x15MMLG	-	-	M16 x 1.5	16	4-8	15
M20x15MMLG	-	-	M20 x 1.5	20	6-12	15
M25x15MMLG	-	-	M25 x 1.5	25	13-18	15

The technical drawing shows a side view of the cable gland with a cable inserted. Dimension D is the thread length, B is the cable die length, and C is the mounting diameter.

Includes O-ring | Includes locknut - RAL 7001 - Dark Grey, RAL 7035 - Light Grey | MMLG (Extra thread length)