



touch pen system for capacitive or resistive touch screen Pen incl. holder for 22.5 mm, screw on or glue for capacitive and resistive touch screens Further information, Quantity and content: see technical data

Figure similar

General information	
Product type designation	Touch pen system capacitive technology
Control elements	
Frame size/design	
• Standard	Yes; For industrial applications
• Exceptional	Yes; Spare caps can be stowed in the pen
• Ergonomic	Yes; With holder
Installation type/mounting	
Mounting type	Wall-mounting bracket can be mounted with mounting disk, 2x M3 screw or adhesive pads
Mounting position	Horizontal
Front mounting	Yes; also optimized for PRO Extension Unit 22.5 mm opening (from HS01)
Wall mounting/direct mounting	Yes
Degree and class of protection	
IP (at the front)	IP65 (depending on mounting)
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased
Ambient temperature during operation	
• min.	-40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
• max.	80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	95 %
Mechanics/material	
Material	
• Plastic	Yes; Attachment cord
• Aluminum	Yes; Touch pen, wall-mounting bracket
Dimensions	
Height	150 mm; Length
Thickness	14 mm; Diameter

Enclosure diameter	37 mm; Diameter wall-mounting bracket
Mounting cutout, height	39 mm; Height wall-mounting bracket
<b>Weights</b>	
Weight without packaging	0.13 kg
Weight incl. packaging	0.14 kg
<b>Scope of supply</b>	
Delivery quantity in pieces	1; 1x touch pen with string, wall-mounting bracket, M6 screw, mounting disk, O-ring, adhesive pads, spare caps for touch pen
<b>Other</b>	
Merchandise	Yes; Function depending on touch sensitivity, not suitable for Ceran cooktops, MP377 Daylight, possibly others
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
Target devices	For common capacitive and resistive touch systems
Note:	Length of the interconnecting lead 53 cm to 100 cm
<b>Usable in the following products</b>	
• Product 21	6AV2124-*

**last modified:**

1/15/2021 