

Flexible Knock Down Bollards Stainless Steel

AB-FLX140-S



Specifications

Dimensions	140mm (DIA) x 1230 mm 300mm Prolypropylene Insert
Base dimensions	240mm x 240mm
Material	4304 Grade Stainless Steel
Installation	Surface mounted (anti-theft & anti tamper)
Additional notes	Bollards comes with a Stainless Steel Cap & Branded Reflective Tape.

Description

Australian Bollards "FLEXIBLE RANGE" properly constructed and fitted will always do its job, protecting people and property. With a fixed rigid bollard it can be ripped from the ground (causing untold damage to the footings and concrete/asphalt) while also damaging the vehicle, sometimes with some expensive repair work required.

This is where our NEW FLEXIBLE BOLLARD comes into play. Our Flexible Bollards have a polypropylene coloured insert which allows impact reflection minimising damage to the vehicle, the footings and the bollard itself.

Once the pressure has been removed, the bollard will snap back to its resting position, ready to do its job again. Testing has proven this bollard reduces damage to the vehicle, while also limiting damage to the bollard and surrounding ground. It's a win-win solution the perfect bollard for high traffic areas - especially forklift, car parks and fast-food driveways. Our Flexible Bollard looks like a regular bollard but in the right situation will stop the headaches that come when protection bollards are struck regularly.

