

Disabled & Wheel Chair Users Car Park Bollard

AB-HI165-1600-DC1-Y



Our Car Park Bollards

Our sub-surface mounted or core drilled Disabled and Wheelchair Users Carpark Bollard is fixed and comes with a high-impact insert, making it ideal for providing maximum protection and safety of disabled access car parks and those accessing them. 300 mm below the surface and 1.3 meters in above-ground height, this 31.5 kg bollard is more robust than its counterpart, the AB-WT165-1300-Y-DC1, and better for people and asset protection in areas where vehicles may travel at higher speeds. Coming metallic powder coated in AB-Yellow or bright blue to stand out, the bollard has branded reflective tape and a reflective wheelchair sticker for improved visibility regardless of time of day. This bollard is optimal for parking spaces on busy roads and shared space car parks.

Specifications

Post Dimensions	165mm Diameter 1300mm Height Above Ground 300mm In Ground
Weight	31.5 kg
Material	Mild Steel. Metallic Powder Coated.
Installation	Sub-Surface Mounted in Concrete or Core-drilled.
Additional Notes	Bollard comes with Disabled Class 1 Reflective Tape, Class 1 Branded Reflective Tape & Stainless Steel Branded Cap. Bollard comes with High Impact Insert. Surface Mounted alternative is the AB-WT165-1300-Y-DC1

