

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

SECTION 1: Identification

1.1 Product identifier

Trade name **Auto Gem Iron Out**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle wheel cleaner

1.3 Details of the supplier of the safety data sheet

Auto Gem Distributing
P.O. Box 169
St. Johns Michigan 48879

517-862-3841
www.autogemdistributing.com
autogemdistributing@yahoo.com

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H317 May cause an allergic skin reaction.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling (2-hydroxyethyl)ammonium mercaptoacetate

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
(2-hydroxyethyl)ammonium mercaptoacetate	CAS No 126-97-6	12 - < 20	Acute Tox. 4 / H302 Skin Sens. 1B / H317
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	1 - < 3	Eye Irrit. 2 / H319
ethoxylated C11-15 secondary alcohols	CAS No 68131-40-8	1 - < 3	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318
benzaldehyde	CAS No 100-52-7	0.1 - < 1	Acute Tox. 4 / H302 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Flam. Liq. 4 / H227

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedings.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	AC-GIH® 2019

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

iv inhalable fraction and vapor

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	DNEL	1.4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	DNEL	2.1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	68 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	68 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethoxylated C11-15 secondary alcohols	68131-40-8	DNEL	42 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethoxylated C11-15 secondary alcohols	68131-40-8	DNEL	6 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
benzaldehyde	100-52-7	DNEL	9.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
benzaldehyde	100-52-7	DNEL	9.8 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
benzaldehyde	100-52-7	DNEL	1.1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	38 µg/l	aquatic organisms	freshwater	short-term (single instance)
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	3.8 µg/l	aquatic organisms	marine water	short-term (single instance)
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	PNEC	3.2 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4 mg/kg	benthic organisms	sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	56 mg/kg	(top) predators	water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	3.9 mg/l	aquatic organisms	water	intermittent release
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.4 mg/kg	pelagic organisms	sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	20 µg/l	aquatic organisms	freshwater	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	2 µg/l	aquatic organisms	marine water	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	8.2 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	28 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	2.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethoxylated C11-15 secondary alcohols	68131-40-8	PNEC	5.6 mg/kg	terrestrial organisms	soil	short-term (single instance)
benzaldehyde	100-52-7	PNEC	0.002 mg/l	aquatic organisms	freshwater	short-term (single instance)
benzaldehyde	100-52-7	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
benzaldehyde	100-52-7	PNEC	7.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
benzaldehyde	100-52-7	PNEC	0.022 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
benzaldehyde	100-52-7	PNEC	0.002 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
benzaldehyde	100-52-7	PNEC	0.003 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless to pale pink
Odor	fruity

Other safety parameters

pH (value)	6 – 8 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	114 °C at 101 kPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	32 hPa at 25 °C
Density	1 g/ml
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200 °C)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	oral	318 mg/kg
ethoxylated C11-15 secondary alcohols	68131-40-8	oral	≥2,000 mg/kg
benzaldehyde	100-52-7	oral	1,430 mg/kg
benzaldehyde	100-52-7	inhalation: vapor	5 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not assigned
14.3	Transport hazard class(es)	not assigned
14.4	Packing group	not assigned
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	carrier fluid / dis-solver	
(2-hydroxyethyl)ammonium mercaptoacetate	126-97-6	metal cleaner	
2-(2-butoxyethoxy)ethanol		co-solvent	CA TACs
sodium gluconate	527-07-1	chelate / se-questrant	
benzaldehyde	100-52-7	fragrance	
isobutyl acetate	110-19-0	fragrance	
isopentyl acetate	123-92-2	fragrance	
Benzyl acetate	140-11-4	fragrance	
propylene glycol	57-55-6	humectant	
citral	5392-40-5	fragrance	

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
2-(2-butoxyethoxy)ethanol		1022			1.0 %

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
2-(2-butoxyethoxy)ethanol			
benzaldehyde	100-52-7		F2

Legend

F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
GLYCOL ETHERS		E

Legend

E Environmental hazard

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 1 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 1 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	Combustible liquid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Auto Gem Iron Out

Version number: GHS 1.0

Date of compilation: 2021-02-10

Code	Text
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.