

With quick disconnect water tank & throttle on guide bar.



## CF2 Honda

### Forward Plate Compactor

The CF 2 offers premium operating comfort and optimum running characteristics for landscape/hardscape professionals or general construction.

With compact dimensions, a folding guide bar and useful handles for lifting the CF2 is easy to transport anywhere. The special low-vibration guide bar (registered design), with user-friendly plastic coating, reduces hand/arm vibrations to ensure pure operational comfort for longer working hours. Now the CF2 also has an easy access throttle directly on the guide bar for extra ease of use.

Practical optional accessories such as: integrated wheel kit, 3.2 gallon easy disconnect water tank for asphalt compaction (flow of water can be adjusted by means of rotary knob) and polyurethane pad further facilitate work.

#### AREAS OF APPLICATION

landscape/hardscape

compacting asphalt or pavers for maintenance

#### ADVANTAGES OF CF2 HONDA:

- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with raised bar on frame
- low hand-arm vibrations
- throttle on guide bar
- water sprinkler system with 3.2 gallon tank (optional).

#### AVAILABLE ACCESSORIES:

- polyurethane pad
- wheel kit
- water sprinkler system (quick disconnect)



#### Technical data

Type	CF2 Honda	
Operating weight CECE	lbs.	183
Operating width	in.	18
Centrifugal force	lbs.	3,372
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-85
Dimensions (L x W x H), in.	in.	44 x 18 x 38

We reserve the right to alter specifications.