



CF3 Honda

Forward Plate Compactor

The CF 3 is for professionals and distinguishes itself by premium operating comfort, compact dimensions and optimum running characteristics.

With compact dimensions, a folding guide bar and useful handles for lifting, the CF3 is easy to transport anywhere. The special low-vibration guide bar (registered design), with user-friendly plastic coating, reduces hand/arm vibrations to ensure pure operational comfort for longer working hours.

Practical optional accessories such as: integrated wheel kit, 3 gallon water tank for asphalt compaction, and polyurethane pad further facilitate work.

AREAS OF APPLICATION

landscape/hardscape

compacting asphalt or pavers for maintenance

Technical data

Type	CF3 Honda	
Operating weight CECE	lbs.	207
Operating width	in.	20
Centrifugal force	lbs.	4,496
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-85
Dimensions (L x W x H), in.	in.	46 x 20 x 38

We reserve the right to alter specifications.

ADVANTAGES OF CF3 HONDA:

- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with raised bar on frame
- low hand-arm vibrations
- throttle on guide bar
- water sprinkler system with 3.2 gallon tank (optional).

AVAILABLE ACCESSORIES:

- polyurethane pad
- wheel kit
- water sprinkler system

