



Hand-Arm-Vibrations < 2,5 m/s²

Technical data

Type	CR3 Honda	
Operating weight CECE	lbs.	448
Operating width	in.	20* / 24 / 28**
Centrifugal force	lbs.	7,868
Frequency	Hz	80
Engine manufacturer / type	Honda	GX 270 (gas)
Engine power output, max.	HP	8.2
Power output at operating speed	HP at rpm	7.0 at 3,000
Working speed (average forward & reverse)	ft/min.	0-66
Dimensions (L x W x H), in.	in.	60 x 20 x 42

*Operating width without standard extension plates.

**Operating width with extension plates (optional).

Bold: with standard extension plates.

We reserve the right to alter specifications.

CR3 Honda

REVERSIBLE SOIL COMPACTOR

State-of-the-art technology, impressive compaction force, and high operational comfort is what you get with the CR3 Honda.

The CR3 combines modern technology, top performance, smooth running characteristics and optimal, especially long-life, quality to guarantee high productivity.

With a compaction force of 7,868 lbs. and weighing only 448 lbs., this machine has high gradeability and the low vibration guide bar also minimizes hard-arm vibrations for extra smooth operation.

The CR3 has flexible working widths. You can take off the standard extensions to create a narrower working width to work in tight spaces. The well-built engine protection frame, self-adjusting centrifugal clutch and easy access to essential maintenance points makes this machine popular for rental fleets. Its long service life and operational reliability are guaranteed.

AREAS OF APPLICATION

trenches	installing interlocking pavers
stone landscape/hardscape	general compaction tasks
road construction	pathways / driveways

ADVANTAGES OF CR3 HONDA:

- low hand-arm vibration and lockable guide bar
- all-around enclosure and sturdy frame to protect engine
- closed v-belt guard
- flexible working widths thanks to extension plates
- quick and safe loading with hinged lifting eye
- eyelets in console for secure lashing and transport
- infinitely variable hydraulic shifting mechanism used for forward & reverse travel
- hydraulic hoses protected within the guide bar
- unobstructed access to all maintenance points
- self-adjusting centrifugal clutch
- hour meter

AVAILABLE ACCESSORIES:

Polyurethane pad
 Extension plates (extends to 28")
 Wheel kit

