



VIBRATORY ROLLER PAVER COMPACTOR



- 1 Folding handle for transport and storage convenience. The handle then acts as engine protection during transport.
- 2 Durable rack and pinion throttle lever. Very smooth operation and stay-in-place settings. This lever is repairable thereby reducing maintenance costs.
- 3 HONDA GX160, a proven, dependable power source
- 4 Rubber coated rollers protect the pavers. Smooth travel over the pavers without chipping the corners and scuffing the paver surface
- 5 Lifting handles for easy loading and unloading.
- 6 Included lifting bail provides a secure lifting point.



MODEL	EVPC120
DIMENSIONS (LxWxH) - in (mm)	26.2 x 26.4 x 47.2 (665 x 670 x 1200)
OPERATING WEIGHT - lbs (kg)	271 (123)
PLATE SIZE (LxW) - in (mm)	25.8 x 24.4 (655 x 620)
VIBRATION FREQUENCY v.p.m. (Hz)	5,640 (94)
CENTRIFUGAL FORCE lbs (kg)	2,315 (1,050)
COMPACTED AREA ft ² /h (m ² /h)	6,458 - 7,534 (600 - 700)
MAX. GRADEABILITY - °	0.8 (3.1)
RUNNING TIME - hours	1.7
ENGINE	HONDA GX160
ENGINE TYPE	4-STROKE GASOLINE
MAX. POWER OUTPUT - kW (hp)	4.8 (3.6)

1-800-417-9272 | ezgmfg.com
 1833 North Riverview Road
 Malta, OH | 43758

